

www.tombling.com

FEATURES:

- · Heavy duty portable fan heaters
- 2 models 3Kw and 5Kw
- 230V Single phase
- 2 meter mains lead with 3 pin plug:

BX3E -13A 3 pin UK plug BS1363

BX5E - 32A plug BS-EN60309

- Built in stand and carrying handle
- Thermostat 0 to 35C
- User control fan only, half power, full power
- Overheat cut-out with manual reset
- IP x4 suitable for use on building sites
- Galvanised steel construction, sealed for life fan motor, and encapsulated stainless steel elements
- Tested and approved to the LVD and EMC directives.
- CE marked
- 2 year guarantee



MODEL	вхзЕ	BX5E
Element rating (W)	3000	5000
Voltage (V)	230V 1 phase	230V 1phase
Power stages (W)	0 - 1500 - 3000	0 - 3300 - 5000
Maximum current (A)	13.2	22
Noise (dBA)	44	47
Airflow (m3/h)	290	500
Max temp rise (C)	29	28
Connection	3 pin 13A UK plug BS1363	3 pin 32A plug BS-EN60309
Weight (kg)	6	6.5
Dimensions w h d (mm)	275 x 320 x 320	275 x 320 x 320
IP rating	IP x4	IP x4

Activair BX portable fan heaters are designed for 230V single phase 50Hz electrical supplies. They are suitable for use in the UK, most of Europe, Eastern Europe and the Middle East, but not the USA.