Model number: VBX5, VBX9, VBX15

Description: Portable fan heaters - 400V 3 phase



www.tombling.com

FEATURES:

| Heavy duty portable fan heaters | | | |
|--|--|--|--|
| 3 models - 5Kw, 9Kw, 15Kw | | | |
| 400V 3 phase & Neutral | | | |
| 2 meter mains lead with BS EN 60309 5 pin plug: | | | |
| VBX5, VBX9 - 16A plug | | | |
| VBX15 - 32A plug | | | |
| Built in stand and carrying handle | | | |
| Thermostat - 0 to 35C | | | |
| User control - fan only, half power, full power | | | |
| Overheat cut-out with manual reset | | | |
| IP X4 - suitable for use on building sites | | | |
| Galvanised steel construction, sealed for life fan motor, and encapsulated stainless steel elements | | | |
| Tested and approved to the LVD and EMC directives. | | | |
| CE marked | | | |

□ 1 year guarantee



| MODEL | VBX5 | VBX9 | VBX15 |
|---------------------------|-------------------------------|-------------------------------|-------------------------------|
| Element rating (W) | 5000 | 9000 | 15000 |
| Voltage (V) | 400V 3 phase | 400V 3 phase | 400V 3 phase |
| Power stages (W) | 0 - 2500 - 5000 | 0 - 4500 - 9000 | 0 - 7500 - 15000 |
| Maximum phase current (A) | 7.4 | 13.3 | 21.9 |
| Noise (dBA) | 47 | 53 | 55 |
| Airflow (m3/h) | 500 | 900 | 1000 |
| Max temp rise (C) | 28 | 28 | 42 |
| Connection | 5 pin 16A BS EN 60309 plug | 5 pin 16A BS EN 60309 plug | 5 pin 32A BS EN 60309 plug |
| Weight (kg) | 6.5 | 10.5 | 15 |
| Dimensions w h d (mm) | 275 x 320 x 320 | 360 x 450 x 370 | 360 x 450 x 370 |
| IP rating | IP X4 | IP X4 | IP X4 |

Activair VBX portable fan heaters are designed for 400V 3 phase 50Hz electrical supplies They are suitable for use in the UK, most of Europe, Eastern Europe and the Middle East, but not the USA.

Our policy is one of continuous improvement and development. Specifications can change at any time. Please contact sales for further information